

## ULTRACORE<sup>®</sup> BRAND SULPHUR CORED WIRE

<b>Grade</b>	<b>S</b>	
<b>Wire diameter:</b>	<b>Ø 13 mm</b>	
<b>Thin wall wire – material &amp; thickness</b>	low-carbon steel band - thickness 0,4 mm	
<b>Core chemical composition:</b>	S	99,85
		100
	% MIN	% MAX
<b>Fill Linear density:</b>	187 ± 6 g / m	
<b>Finished coil parameters:</b>		
inner diameter of coil	600 <sup>+10</sup> mm	
outer diameter of coil	max 1350 mm	max 800 mm
coil width	800 <sup>+20</sup> mm	400 <sup>+20</sup> mm
coil wire length	1000 ÷ 5700 m	500 ÷ 1800 m
coil total weight	500 ÷ 2200 kg	250 ÷ 600 kg
<b>Packing:</b>	on wooden pallets, in steel baskets or loose, Axis orientation axis - horizontal or vertical	
<b>Identification:</b>	Coil identifier and finished product tag	
<b>Storage:</b>	covered in dry room - protected against atmospheric conditions	
<b>Transportation:</b>	covered means of transport	
<b>Application:</b>	for production of steel with regulated sulfur contents	
<i>Real parameters of wire for each coil are enclosed with finished product tag. This sheet is valid since 27 September 2005</i>		

### MATERIAL SAFETY DATA SHEET:

Available to Globe customers. Please ask your sales representative

REV-Aug/07